



BARGE "MM 82"

INNAGE (HERMETIC)

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
1 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
2 PORT	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4
2 STBD	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4
3 PORT	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4
3 STBD	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4
4 PORT	- 00-3/4	00-3/4	- 01-1/2	01-1/2	- 02-1/4	02-1/4	- 03-0/8	03-0/8	- 03-3/4	03-3/4	- 04-1/2	04-1/2
4 STBD	- 00-3/4	00-3/4	- 01-1/2	01-1/2	- 02-1/4	02-1/4	- 03-0/8	03-0/8	- 03-3/4	03-3/4	- 04-1/2	04-1/2

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 PORT IS - 00-1/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 2 PORT, THE TRIM CORRECTED INNAGE IS 3'-11 7/8'

LENGTH BETWEEN DRAFT MARKS: 237'-00"

April 14, 2014

PRECISION MEASUREMENT
& ANALYSIS, INC.

P.O. Box 2092
Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "MM 82"

INNAGE (8" HATCH)

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-1/2	00-1/2	- 00-1/2	00-1/2
1 STBD	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-1/2	00-1/2	- 00-1/2	00-1/2
2 PORT	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-3/8	00-3/8
2 STBD	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-3/8	00-3/8
3 PORT	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-1/2	00-1/2	- 00-3/4	00-3/4	- 00-7/8	00-7/8
3 STBD	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-1/2	00-1/2	- 00-3/4	00-3/4	- 00-7/8	00-7/8
4 PORT	- 00-7/8	00-7/8	- 01-3/4	01-3/4	- 02-5/8	02-5/8	- 03-3/8	03-3/8	- 04-1/4	04-1/4	- 05-1/8	05-1/8
4 STBD	- 00-7/8	00-7/8	- 01-3/4	01-3/4	- 02-5/8	02-5/8	- 03-3/8	03-3/8	- 04-1/4	04-1/4	- 05-1/8	05-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 PORT IS 00-1/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 2 PORT, THE TRIM CORRECTED INNAGE IS 4'-00 1/8'

LENGTH BETWEEN DRAFT MARKS: 237'-00"

April 14, 2014

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "MM 82"
MAGNOLIA BARGE

3 STBD
INNAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

GAUGE HEIGHT 11'-08 1/4"

Table with 18 columns (0 FT. to 10 FT.) and 28 rows (0 to 3/4). Each cell contains capacity values for different gauge heights and deck positions.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.
CAPACITY TABLE EXTENDS TO EXTERNAL HEIGHT OF TANK.
CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES.
GAUGE POINT: (HERMETIC - 2" VALVE) LOCATED 12'-09" OFF CENTERLINE AND 33'-06" FORWARD OF AFT BULKHEAD.
GAUGE POINT: (8" HATCH) LOCATED 12'-09" OFF CENTERLINE AND 35'-06" FORWARD OF AFT BULKHEAD

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 04/14/2014 CL
CALCULATED: 04/14/2014 CL
PRINTED: 04/14/2014 CL

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
http://www.pmacorp.net

Signature of PMA representative

CANCELS AND SUPERCEDES
ALL PRIOR TO 04/20/14



BARGE "MM 82"

ULLAGE (HERMETIC)

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8
2 PORT	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4
2 STBD	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/4	00-1/4
3 PORT	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4
3 STBD	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4
4 PORT	00-3/4	- 00-3/4	01-1/2	- 01-1/2	02-1/4	- 02-1/4	03-0/8	- 03-0/8	03-3/4	- 03-3/4	04-1/2	- 04-1/2
4 STBD	00-3/4	- 00-3/4	01-1/2	- 01-1/2	02-1/4	- 02-1/4	03-0/8	- 03-0/8	03-3/4	- 03-3/4	04-1/2	- 04-1/2

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 PORT IS 00-1/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 2 PORT, THE TRIM CORRECTED ULLAGE IS 4'-00 1/8"

LENGTH BETWEEN DRAFT MARKS: 237'-00"

April 14, 2014

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "MM 82"

ULLAGE (8" HATCH)

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-1/2	- 00-1/2
1 STBD	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-1/2	- 00-1/2
2 PORT	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-3/8	- 00-3/8
2 STBD	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-3/8	- 00-3/8
3 PORT	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-3/4	- 00-3/4	00-7/8	- 00-7/8
3 STBD	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-3/4	- 00-3/4	00-7/8	- 00-7/8
4 PORT	00-7/8	- 00-7/8	01-3/4	- 01-3/4	02-5/8	- 02-5/8	03-3/8	- 03-3/8	04-1/4	- 04-1/4	05-1/8	- 05-1/8
4 STBD	00-7/8	- 00-7/8	01-3/4	- 01-3/4	02-5/8	- 02-5/8	03-3/8	- 03-3/8	04-1/4	- 04-1/4	05-1/8	- 05-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 PORT IS - 00-1/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 2 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11 7/8"

LENGTH BETWEEN DRAFT MARKS: 237'-00"

April 14, 2014

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "MM 82"
MAGNOLIA BARGE

3 PORT
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

GAUGE HEIGHT 11'-08 1/4"

Table with 17 columns representing gauge heights (1 FT. to 11 FT.) and 17 rows representing different barge configurations. Each cell contains a numerical value representing capacity in barrels.

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.
CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.
CAPACITY TABLE ONLY APPLIES TO ULLAGE GAUGES.
GAUGE POINT: (HERMETIC - 2" VALVE) LOCATED 12'-09" OFF CENTERLINE AND 33'-08" FORWARD OF AFT BULKHEAD.
GAUGE POINT: (8" HATCH) LOCATED 12'-09" OFF CENTERLINE AND 35'-06" FORWARD OF AFT BULKHEAD

STRAPPED: 04/14/2014 CL
CALCULATED: 04/14/2014 CL
PRINTED: 04/14/2014 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 04/2014

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
http://www.pmacorp.net



BARGE "MM 82"
MAGNOLIA BARGE

3 STBD
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

GAUGE HEIGHT 11'-08 1/4"

Table with columns for height (1 FT. to 11 FT.) and rows for various gauge heights (0 to 34). Each cell contains capacity values in barrels.

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.
CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.
CAPACITY TABLE ONLY APPLIES TO ULLAGE GAUGES.
GAUGE POINT: (HERMETIC - 2" VALVE) LOCATED 12'-09" OFF CENTERLINE AND 33'-06" FORWARD OF AFT BULKHEAD.
GAUGE POINT: (B* HATCH) LOCATED 12'-09" OFF CENTERLINE AND 35'-06" FORWARD OF AFT BULKHEAD.

STRAPPED: 04/14/2014 CL
CALCULATED: 04/14/2014 CL
PRINTED: 04/14/2014 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 04/2014

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
http://www.pmacorp.net

Signature

