



BARGE "MM 74"
MAGNOLIA MARINE

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4505

Table with columns for gauge height (0 FT. to 14 FT.) and rows for measurement points (0, 1/4, 1/2, 3/4) at each height. Includes numerical capacity values and a note 'STRAPPED: 10/25/05' at the bottom right.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 10/25/05

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 11'-11 1/2" (RIM OF HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

BARGE "MM-74"

MAGNOLIA MARINE

HULL NO. 4505

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(+) 0' - 0 1/8"	NIL	NIL
1'-0"	(+) 0' - 0 1/8"	(+) 0' - 0 1/8"	NIL
1'-6"	(+) 0' - 0 1/4"	(+) 0' - 0 1/8"	(-) 0' - 0 1/8"
2'-0"	(+) 0' - 0 3/8"	(+) 0' - 0 1/8"	(-) 0' - 0 1/8"
2'-6"	(+) 0' - 0 3/8"	(+) 0' - 0 1/4"	(-) 0' - 0 1/8"
3'-0"	(+) 0' - 0 1/2"	(+) 0' - 0 1/4"	(-) 0' - 0 1/8"
3'-6"	(+) 0' - 0 5/8"	(+) 0' - 0 3/8"	(-) 0' - 0 1/8"
4'-0"	(+) 0' - 0 5/8"	(+) 0' - 0 3/8"	(-) 0' - 0 1/4"
4'-6"	(+) 0' - 0 3/4"	(+) 0' - 0 3/8"	(-) 0' - 0 1/4"
5'-0"	(+) 0' - 0 7/8"	(+) 0' - 0 1/2"	(-) 0' - 0 1/4"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 10/25/05

BY: _____

INSPECTORATE AMERICA CORPORATION