

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92

MAGNOLIA MARINE - BARGE "MM 48"

OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL 4046

Table with 18 columns (0 FEET to 12 FEET, FEET) and 18 rows (0 to 11). Each cell contains a gauge number and a numerical value. The table is organized into sections for each gauge height (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11).

CAPACITY IN: 42-GALLON BARRELS

GAUGE HEIGHT: 12'-10" (RIM OF HATCH OPPOSITE HINGE LOCATED NEAR CENTER OF TANK)

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92

MAGNOLIA MARINE - BARGE "MM 48"

OUTAGE TABLE

4 PORT

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL 4046

1 FEET	2 FEET	3 FEET	4 FEET	5 FEET	6 FEET	7 FEET	8 FEET	9 FEET	10 FEET	11 FEET	12 FEET	13 FEET	FEET
IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.
0	0	0	0	0	0	0	0	0	0	0	0	0	0
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
1	1	1	1	1	1	1	1	1	1	1	1	1	1
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
2	2	2	2	2	2	2	2	2	2	2	2	2	2
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
3/4	2625.67	3/4	2605.18	3/4	2567.99	3/4	2376.14	3/4	2114.35	3/4	1852.55	3/4	1590.76
3	3	3	3	3	3	3	3	3	3	3	3	3	3
1/4	2625.59	1/4	2603.89	1/4	2563.08	1/4	2365.23	1/4	2103.44	1/4	1841.65	1/4	1579.85
1/2	2625.55	1/2	2603.25	1/2	2560.62	1/2	2359.78	1/2	2097.98	1/2	1836.19	1/2	1574.40
3/4	2625.51	3/4	2602.61	3/4	2558.17	3/4	2354.32	3/4	2092.53	3/4	1830.74	3/4	1568.95
4	4	4	4	4	4	4	4	4	4	4	4	4	4
1/4	2625.27	1/4	2601.33	1/4	2551.34	1/4	2343.41	1/4	2081.62	1/4	1819.83	1/4	1558.04
1/2	2625.15	1/2	2600.69	1/2	2547.92	1/2	2337.96	1/2	2076.17	1/2	1814.38	1/2	1552.58
3/4	2625.03	3/4	2600.05	3/4	2544.51	3/4	2332.51	3/4	2070.71	3/4	1808.92	3/4	1547.13
5	5	5	5	5	5	5	5	5	5	5	5	5	5
1/4	2624.63	1/4	2598.77	1/4	2536.71	1/4	2321.60	1/4	2059.81	1/4	1798.01	1/4	1536.22
1/2	2624.43	1/2	2598.12	1/2	2532.81	1/2	2316.14	1/2	2054.35	1/2	1792.56	1/2	1530.77
3/4	2624.23	3/4	2597.48	3/4	2528.91	3/4	2310.69	3/4	2048.90	3/4	1787.11	3/4	1525.31
6	6	6	6	6	6	6	6	6	6	6	6	6	6
1/4	2623.67	1/4	2596.20	1/4	2521.12	1/4	2299.78	1/4	2037.99	1/4	1776.20	1/4	1514.41
1/2	2623.39	1/2	2595.56	1/2	2517.22	1/2	2294.33	1/2	2032.54	1/2	1770.74	1/2	1508.95
3/4	2623.12	3/4	2594.92	3/4	2513.32	3/4	2288.87	3/4	2027.08	3/4	1765.29	3/4	1503.50
7	7	7	7	7	7	7	7	7	7	7	7	7	7
1/4	2622.40	1/4	2593.64	1/4	2505.53	1/4	2277.97	1/4	2016.17	1/4	1754.38	1/4	1492.59
1/2	2622.04	1/2	2593.00	1/2	2501.63	1/2	2272.51	1/2	2010.72	1/2	1748.93	1/2	1487.14
3/4	2621.68	3/4	2592.36	3/4	2497.73	3/4	2267.06	3/4	2005.27	3/4	1743.47	3/4	1481.68
8	8	8	8	8	8	8	8	8	8	8	8	8	8
1/4	2620.80	1/4	2591.07	1/4	2489.93	1/4	2256.15	1/4	1994.36	1/4	1732.57	1/4	1470.77
1/2	2620.36	1/2	2590.43	1/2	2486.04	1/2	2250.70	1/2	1988.90	1/2	1727.11	1/2	1465.32
3/4	2619.92	3/4	2589.79	3/4	2482.14	3/4	2245.24	3/4	1983.45	3/4	1721.66	3/4	1459.87
9	9	9	9	9	9	9	9	9	9	9	9	9	9
1/4	2618.88	1/4	2588.51	1/4	2474.34	1/4	2234.33	1/4	1972.54	1/4	1710.75	1/4	1448.96
1/2	2618.36	1/2	2587.87	1/2	2470.44	1/2	2228.88	1/2	1967.09	1/2	1705.30	1/2	1443.50
3/4	2617.84	3/4	2587.23	3/4	2466.55	3/4	2223.43	3/4	1961.63	3/4	1699.84	3/4	1438.05
10	10	10	10	10	10	10	10	10	10	10	10	10	10
1/4	2616.63	1/4	2585.95	1/4	2458.75	1/4	2212.52	1/4	1950.73	1/4	1688.93	1/4	1427.14
1/2	2616.03	1/2	2585.30	1/2	2454.85	1/2	2207.06	1/2	1945.27	1/2	1683.48	1/2	1421.69
3/4	2615.43	3/4	2584.66	3/4	2450.95	3/4	2201.61	3/4	1939.82	3/4	1678.03	3/4	1416.23
11	11	11	11	11	11	11	11	11	11	11	11	11	11
1/4	2614.15	1/4	2583.38	1/4	2443.16	1/4	2190.70	1/4	1928.91	1/4	1667.12	1/4	1405.33
1/2	2613.51	1/2	2582.74	1/2	2439.26	1/2	2185.25	1/2	1923.46	1/2	1661.66	1/2	1399.87
3/4	2612.87	3/4	2582.10	3/4	2435.36	3/4	2179.79	3/4	1918.00	3/4	1656.21	3/4	1394.42

CAPACITY IN: 42-GALLON BARRELS

GAUGE HEIGHT: 13'-3 1/4" (RIM OF HATCH OPPOSITE HINGE LOCATED NEAR CENTER OF TANK)

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92

*CAPACITY BELOW STRIKE POINT

STRAPPED 11/5/92